




JRC-T Series 12000W Transient Voltage Suppressor

Rev.2.3

DESCRIPTION:

The JRC-T series of high current uni/bi-directional transient suppressors are designed for high power DC bus clamping applications. These devices offer uni/bi-directional port protection from 20 volts to 72 volts. They provide a clamping voltage lower than the avalanche voltage. Therefore, any voltage rise due to increased current conduction is contained to a minimum, providing the best possible protection level. They can also be connected in series and/or parallel to create very high capacity protection solutions.



FEATURES:

- ✧ Low incremental surge resistance.
- ✧ Excellent clamping capability.
- ✧ Typical I_R less than $5\mu A$ above 22V.
- ✧ Color band denoted cathode except bidirectional.
- ✧ High temperature soldering: $265^{\circ}C/10s$ at terminals.
- ✧ Plastic package has underwriters laboratory flammability 94V-0.
- ✧ 12000W peak pulse power capability at 10/1000 μs waveform.
- ✧ Fast response time: typically less than 1.0ps from 0V to V_{BR} min.
- ✧ Terminal: solder plated, solderable per J-STD-002.
- ✧ UL 497B item recognized. (File No.:E480698).
- ✧ High reliability application and automotive grade (AEC-Q101 qualified).

IEC COMPATIBILITY

- ✧ ISO16750-2 P5A12V system (DC14V 87V/0.5 Ω /400ms).
- ✧ ISO16750-2 P5A 24V system (DC28V 174V/2 Ω /350ms).

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}C$, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +175	$^{\circ}C$
Peak pulse power dissipation on 10/1000 μs waveform	P_{PP}	12000	W
Steady state power dissipation at $T_L=75^{\circ}C$	$P_{M(AV)}$	8	W

ABSOLUTE MAXIMUM RATINGS (T_A=25°C, RH=45%-75%, unless otherwise noted, continued)

Parameter	Symbol	Value	Unit
Maximum instantaneous forward voltage at 100A for unidirectional only	V _F	5	V
Peak forward surge current, 8.3ms single half sine-wave	I _{FSM}	600	A
Typical thermal resistance junction to lead	R _{θJL}	8.0	°C/W
Typical thermal resistance junction to ambient	R _{θJA}	40	°C/W

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Part Number		V _R	I _{R@V_R}	V _{BR@I_T}		I _T	V _{C@I_{PP}}	I _{PP} ^①
Uni-Polar	Bi-Polar	V	μA	min(V)	max(V)	mA	max(V)	A
JRC-T20A	JRC-T20CA	20.0	15	22.20	24.50	5	34.3	349.9
JRC-T22A	JRC-T22CA	22.0	10	24.40	26.90	5	37.1	323.5
JRC-T24A	JRC-T24CA	24.0	5	26.70	29.50	5	40.7	294.9
JRC-T26A	JRC-T26CA	26.0	5	28.90	31.90	5	44.0	272.8
JRC-T28A	JRC-T28CA	28.0	5	31.10	34.40	5	47.5	252.7
JRC-T30A	JRC-T30CA	30.0	5	33.30	36.80	5	50.7	236.7
JRC-T33A	JRC-T33CA	33.0	5	36.70	40.60	5	54.7	219.4
JRC-T36A	JRC-T36CA	36.0	5	40.00	44.20	5	59.8	200.7
JRC-T40A	JRC-T40CA	40.0	5	44.40	49.10	5	65.8	182.4
JRC-T43A	JRC-T43CA	43.0	5	47.80	52.80	5	69.8	171.9
JRC-T48A	JRC-T48CA	48.0	5	53.60	58.70	5	77.7	154.5
JRC-T58A	JRC-T58CA	58.0	5	64.40	71.20	5	93.6	128.2
JRC-T64A	JRC-T64CA	64.0	5	71.10	78.60	5	103	116.5
JRC-T72A	JRC-T72CA	72.0	5	80.00	88.50	5	116	103.4

① Surge waveform:10/1000μs

V_R: Stand-off voltage -- Maximum voltage that can be applied

V_{BR}: Breakdown voltage

V_C: Clamping voltage -- Peak voltage measured across the suppressor at a specified I_{PP}

I_R: Reverse leakage current

RATINGS AND V-I CHARACTERISTICS CURVES (T_A=25°C, unless otherwise noted)

FIG.1:V- I curve characteristics (Uni-directional)




FIG.2:V- I curve characteristics (Bi-directional)




FIG.3: Pulse waveform






FIG.4: Pulse derating curve




SOLDERING PARAMETERS

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min (T _{s(min)})	+150°C
	-Temperature Max(T _{s(max)})	+200°C
	-Time (Min to Max) (t _s)	60-180 secs.
Average ramp up rate (Liquidus Temp (T _L)to peak)		3°C/sec. Max
T _{s(max)} to T _L - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature(T _L)(Liquidus)	+217°C
	-Temperature(t _L)	60-150 secs.
Peak Temp (T _p)		+260(+0/-5)°C
Time within 5°C of actual Peak Temp (t _p)		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp (T _p)		8 min. Max
Do not exceed		+260°C




Flow/Wave Soldering(Solder Dipping)	
Peak temperature	265°C
Dipping time	10 sec.
Soldering	1 time

MARKING & ORDERING INFORMATION



PACKAGE MECHANICAL DATA

 <p>R6</p>	Ref.	Dimensions			
		Millimeters		Inches	
		Min.	Max.	Min.	Max.
	A	25.40	-	1.000	-
B	8.60	9.40	0.339	0.370	
C	1.20	1.40	0.047	0.055	
D	8.60	9.10	0.339	0.358	

PART No.	UNIT WEIGHT (g/PCS) typ.	CASE TYPE	QUANTITY (PCS)	PACKING OPTION
JRC-TxxA/CA	3.25	R-6/P-600	300	Box

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 2.3rd version which is made in 18-July-2019. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright©2019 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.