




## JECR0806AL-D

## TANDEM EPI HYPERFAST RECOVERY RECTIFIER

Rev.1.1

## DESCRIPTION

- ✧ Plastic package has underwriters laboratory flammability classification 94V-0
- ✧ Lead free in comply with EU RoHS 2011/65/EU directives
- ✧ Low reverse leakage current
- ✧ Hyperfast recovery time and soft recovery characteristics
- ✧ Low recovery loss
- ✧ Internal ceramic insulated devices with equal thermal conditions for both 300V diodes
- ✧ Applications for continuous current mode (CCM) power factor correction (PFC)
- ✧ Insulation (2500V<sub>RMS</sub>) allows placement on same heatsink as mosfet and flexible heatsinking on common or separate heatsink



## MECHANICAL DATA

- ✧ Case: TO-220A-2L molded plastic over passivated junction
- ✧ Terminals: Solder plated, solderable per J-STD-002
- ✧ Internally constructed isolated package is offered for ease of heat sinking with highest isolation voltage
- ✧ Weight: 2.1gram

## ABSOLUTE MAXIMUM RATING (Rating at 25°C case temperature unless otherwise specified.)

Parameter	Symbol	JECR0806AL-D	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	600	V
Maximum RMS voltage	V <sub>RMS</sub>	420	V
Maximum DC blocking voltage	V <sub>DC</sub>	600	V
Maximum average forward current at T <sub>c</sub> =100°C	I <sub>F(AV)</sub>	8	A
Peak forward surge current: 10ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	150	A
Junction temperature and storage temperature range	T <sub>j</sub> , T <sub>stg</sub>	-55 to +175	°C



## ISOLATION CHARACTERISTICS

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$V_{\text{isol(RMS)}}$	RMS isolation voltage	50Hz≤f≤60Hz;RH≤65%;from all pins to external heatsink; sinusoidal waveform; clean and dust free	-	-	2500	V
$C_{\text{isol}}$	Isolation capacitance	from cathode to external heatsink	-	10	-	pF

## ELECTRICAL CHARACTERISTICS(Rating at 25°C case temperature unless otherwise specified.)


Parameter		Symbol	Min.	Typ.	Max.	Unit
Forward voltage	$I_F=8A, T_j=25^\circ C$	$V_F$	-	-	3.6	V
	$I_F=8A, T_j=150^\circ C$		-	1.95	2.4	
Reverse current at rated DC blocking voltage	$T_j=25^\circ C$	$I_R$	-	-	5	$\mu A$
	$T_j=150^\circ C$		-	-	200	
Reverse recovery time	$I_F=0.5A, I_{rr}=0.25A, I_R=1A, T_j=25^\circ C$	$t_{rr}$	-	13	-	ns
	$I_F=1A, V_R=30V, di/dt=-50A/\mu s, T_j=25^\circ C$		-	-	30	
Peak reverse recovery current	$I_F=8A, V_R=400V, di/dt=-200A/\mu s, T_j=125^\circ C$	$I_{RM}$	-	4	5.5	A
Recovered charge	$I_F=8A, V_R=400V, di/dt=-200A/\mu s, T_j=125^\circ C$	$Q_r$	-	50	-	nC
Reverse recovery softness factor	$I_F=8A, V_R=400V, di/dt=-200A/\mu s, T_j=125^\circ C$	S	-	0.4	-	-

## THERMAL RESISTANCES

Symbol	Parameter	Min.	Typ.	Max.	Unit
$R_{\text{th(j-c)}}$	Thermal resistance from junction to case	-	2.6	-	°C/W



## MARKING



ECR	EPI Hyperfast Recovery Rectifier
08	$I_{F(AV)}=8A$
06	$V_{RRM}:600V$
AL	Package:TO-220A-2L
D	Double chip

xH1: Month, 1、2、3 ~ 9、A、B、C

3x1:


2018	2019	2020	2021	2022	2023	2024
H	I	J	K	L	M	N
2025	2026	2027	2028	2029	2030	...
O	P	Q	R	S	T	...

3Hx: Batch number

## ORDERING INFORMATION

J	E	C	R	08	06	AL	-D
JIEJIE Microelectronics	EPI	Hyperfast	Rectifier				Double chip
						Package: TO-220A-2L	
				$I_{F(AV)}=8A$	$V_{RRM}:600V$		

## PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.61		0.88	0.024		0.035
C	0.46		0.70	0.018		0.028
C2	1.21		1.32	0.048		0.052
C3	2.40		2.72	0.094		0.107
D	8.60		9.70	0.339		0.382
E	9.80		10.4	0.386		0.409
F	6.55		6.95	0.258		0.274
G		5.08			0.1	
H	28.0		29.8	1.102		1.173
L1		3.75			0.148	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
V1		45°			45°	

## PACKAGE INFORMATION-TO-220A-2L

OUTLINE	UNIT WEIGHT (g/PCS) typ.	TUBE (PCS)	PER CARTON (PCS)
TUBE	2.1	50	5,000

## CHARACTERISTICS CURVE

FIG.1: Typical forward characteristics




FIG.2: Typical reverse characteristics




FIG.3: Maximum non-repetitive peak forward surge current




FIG.4: Forward current derating curve






FIG.5: Forward power dissipation vs. average forward current (square waveform)





FIG.6: Reverse recovery definitions



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 1.1st version which is made in 20-July-2021. This document supersedes and replaces all information previously supplied.



JieJie is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2021 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserve.