


**DESCRIPTION:**

With high ability to withstand the shock loading of large current, JCT1225 SCRs provide high dv/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc.

From all three terminals to external heatsink, JCT1225A provides a rated insulation voltage of 2500 V_{RMS}, and JCT1225F provides a rated insulation voltage of 2000 V_{RMS}, complying with UL standards (File ref: E252906). Packages listed above are RoHS compliant. (2011/65/EU)

MAIN FEATURES

Symbol	Value	Unit
V _{DRM} / V _{RRM}	1200	V
I _{T(RMS)}	25	A
I _{GT}	≤ 40	mA

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit	
Storage junction temperature range	T _{stg}	-40-150	°C	
Operating junction temperature range	T _j	-40-125	°C	
Repetitive peak off-state voltage(T _j =25°C)	V _{DRM}	1200	V	
Repetitive peak reverse voltage(T _j =25°C)	V _{RRM}	1200	V	
Average on-state current	I _{T(AV)}	16	A	
RMS on-state current	TO-220A (Ins)/ TO-220F (Ins) (T _c =85°C) TO-220B (Non-Ins)/ TO-220C (T _c =100°C)	I _{T(RMS)}	25	A

Non repetitive surge peak on-state current (tp=10ms)	I _{TSM}	300	A
I ² t value for fusing (tp=10ms)	I ² t	450	A ² s
Critical rate of rise of on-state current (I _G =2×I _{GT})	dI/dt	150	A/μs
Peak gate current	I _{GM}	4	A
Average gate power dissipation	P _{G(AV)}	2	W
Peak gate power	P _{GM}	5	W

ELECTRICAL CHARACTERISTICS (T_j=25°C unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I _{GT}	V _D =12V R _L =33Ω	-	-	40	mA
V _{GT}		-	-	1.5	V
V _{GD}	V _D =V _{DRM} T _j =125°C R _L =3.3KΩ	0.2	-	-	V
I _L	I _G =1.2I _{GT}	-	-	140	mA
I _H	I _T =500mA	-	-	120	mA
dV/dt	V _D =2/3V _{DRM} Gate Open T _j =125°C	1000	-	-	V/μs

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)	Unit
V _{TM}	I _{TM} =50A tp=380μs	T _j =25°C	1.6	V
I _{DRM}	V _D =V _{DRM} V _R =V _{RRM}	T _j =25°C	10	μA
I _{RRM}		T _j =125°C	4	mA


THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
R _{th(j-c)}	junction to case(AC)	TO-220A(Ins)	1.4
		TO-220B (Non-Ins) / TO-220C	0.85
		TO-220F(Ins)	1.5

ORDERING INFORMATION


J	CT	12	25	B
JieJie Microelectronics Co.,Ltd				C:TO-220C A:TO-220A(Ins) F:TO-220F(Ins) B:TO-220B (Non-Ins)
	SCRs			
		12:V _{DRM} / V _{RRM} ≥ 1200V		I _{T(RMS)} :25A

PACKAGE MECHANICAL DATA




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.61		0.88	0.024		0.035
C	0.46		0.70	0.018		0.028
C2	1.21		1.32	0.048		0.052
C3	2.40		2.72	0.094		0.107
D	8.60		9.70	0.339		0.382
E	9.80		10.4	0.386		0.409
F	6.55		6.95	0.258		0.274
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.75			0.148	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
V1		45°			45°	

PACKAGE MECHANICAL DATA




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.61		0.88	0.024		0.035
C	0.46		0.70	0.018		0.028
C2	1.21		1.32	0.048		0.052
C3	2.40		2.72	0.094		0.107
D	8.60		9.70	0.339		0.382
E	9.60		10.4	0.378		0.409
F	6.20		6.60	0.244		0.260
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.75			0.148	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
V1		45°			45°	



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.23		1.32	0.048		0.052
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.3	0.390		0.406
F	6.30		6.90	0.248		0.272
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.39			0.133	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
Φ		3.6			0.142	

PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.50		4.90	0.177		0.193
B	0.74	0.80	0.83	0.029	0.031	0.033
C	0.47		0.65	0.019		0.026
C2	2.45		2.75	0.096		0.108
C3	2.60		3.00	0.102		0.118
D	8.80		9.30	0.346		0.366
E	9.80		10.4	0.386		0.410
F	6.40		6.80	0.252		0.268
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.63			0.143	
L2	1.14		1.70	0.045		0.067
L3		3.30			0.130	
V1		45°			45°	

PACKAGE INFORMATION

PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-220A	TUBE	50	1,000	5,000
TO-220B	TUBE	50	1,000	5,000
TO-220C	TUBE	50	1,000	5,000
TO-220F	TUBE	50	1,000	5,000

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature






FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $tp < 10\text{ms}$, and corresponding value of I^2t ($dI/dt < 150\text{A}/\mu\text{s}$)




FIG.4: On-state characteristics (maximum values)





FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the eighth version which is made in 24-July-2020. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2020 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.